


バーチカルフック

品番	個(箱)	L x Ø mm	R mm	V °	D mm	耐荷重(kg)
V680X3,0 PR50D10	800	680X3,0	4	50°	10	25
V680X3,5 PR30D15	700	680X3,5	4	30°	15	30
V680X3,5 PR50D15	700	680X3,5	4	50°	15	30
V680X4,0 PR30D20	500	680X4,0	4	30°	20	45

- » フックの上部がハンガーに掛けやすい形状になっています。
- » ワーク吊り下げ部は2種類の角度をご用意しております。




フック (ロボット用) 鉄

品番	個(箱)	L X φ mm	A mm	B mm
F050X1,5 PDVX2	7,500 ※	050X1,5	17	15
F050X2,0 PDVX2	5,500 ※	050X2,0	17	15
F060X1,5 PDVX2	7,500 ※	060X1,5	17	15
F060X2,0 PDVX2	5,500 ※	060X2,0	17	15
F075X1,5 PDVX2	6,000 ※	075X1,5	17	15
F075X2,0 PDVX2	4,400 ※	075X2,0	17	15
F100X1,5 PDVX2	6,000 ※	100X1,5	17	15
F100X2,0 PDVX2	4,400 ※	100X2,0	17	15
F120X2,0 PDVX2	4,400 ※	120X2,0	17	15

- » フックを束ねてテープで固定しています。

スタンダードフック PTRVX2 鉄



品番	個(箱)	L X φ mm	A mm	B mm	C mm
050X2,0 PTRVX2	4,000 ※	050X2,0	14	11	13
060X2,0 PTRVX2	4,000 ※	060X2,0	14	11	13
075X2,0 PTRVX2	3,000 ※	075X2,0	14	11	13
075X3,0 PTRVX2	2,000 ※	075X3,0	15	12	14
100X2,0 PTRVX2	2,000 ※	100X2,0	14	11	13
100X3,0 PTRVX2	1,500 ※	100X3,0	15	12	14
150X2,0 PTRVX2	1,200 ※	150X2,0	14	11	13
150X3,0 PTRVX2	700 ※	150X3,0	15	12	14
200X3,0 PTRVX2	800 ※	200X3,0	15	12	14
400X3,0 PTRVX2	600 ※	400X3,0	15	12	14
500X3,0 PTRVX2	500 ※	500X3,0	15	12	14